

Product Name:	CRTPR051WWGLH/0
Description:	<p>Undercounter Controlled Room Temperature Cabinet, Built-In-LEFT HINGED</p> <p>4.6 Cu. Ft. Capacity</p> <p>One glass swing door, left hinged</p> <p>Microprocessor temperature controller</p> <p>Digital temperature display</p> <p>Audible and visual high and low temperature alarms</p> <p>Remote alarm contacts</p> <p>2 probes; 1 in air and 1 in sample bottle</p> <p>Adjustable operating temperature range: 68°F–77°F (20°C – 25°C)</p> <p>Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory, F/C switchable, field installable, and visual &amp; audible temp alarm</p> <p>Three shelves (two adjustable/one fixed) with guard rail on back to prevent product from pushing against back wall</p> <p>Back wall evaporator cover</p> <p>Vaccine storage power cord warning label</p> <p>Forced draft circulation</p> <p>Keyed door lock</p> <p>Magnetic door gasket for positive seal</p> <p>Leveling legs</p> <p>LED interior light</p> <p>Probe access port (3/8")</p> <p>Powder coat exterior</p> <p>High density urethane foam cabinet and door insulation</p> <p>HFC-free refrigerant (R600a), foam insulation and packaging</p> <p>Two year parts and labor warranty, plus an additional three year compressor parts only warranty</p> <p>Pyxis<sup>®</sup>, Omnicell<sup>®</sup> and AcuDose RX<sup>®</sup> compatible</p> <p>Exterior dimensions: 23 ¾" W x 25 ½" D x 33 3/8" H</p> <p>Cycle defrost</p> <p>115V, 60 Hz, 1.74 Amps, 1/8 HP</p> <p>ENERGY STAR CERTIFIED</p> <p>UL/C-UL listed</p> <p>Shipping weight: 150 lbs.</p>