

Product Name:	ERF302WWW/0
Description:	<p>General Purpose Hazardous Location (Explosion Proof) Refrigerator/Freezer Combination  30 Cu. Ft. Capacity (25 Ref./5 Freezer)  One solid swing door/one interior solid swing door-freezer chamber only, right hinged, not reversible  Mechanical thermostat sealed in UL listed explosion proof box  Adjustable operating temperature range: Refrigerator: 1°C – 10°C  Freezer: -15°C – -25°C  Three adjustable refrigerator shelves  Keyed door lock  Magnetic door gasket for positive seal  Stainless steel door handle  Leveling legs  White textured cabinet and door  High density urethane foam cabinet and door insulation  CFC-free refrigerant (R404a), foam insulation and packaging  Exterior dimensions: 35 ¾"W x 36 ¼"D x 77 ½"H  Manual defrost  Not equipped with line cord and plug; must be hardwired in conduit to 120 VAC power source  115V, 60Hz, 6 Amps, 1/3 HP  UL/C-UL listed  One year parts and labor warranty  Meet NFPA and OSHA guidelines for hazardous locations, Class 1, Division II, Groups C &amp; D.  These units are not intended for use in general clinical or research laboratories.  Shipping weight: 408 lbs.</p>