Product Name:	FR301WWW/0TS
Description:	Corepoint Scientific™ White Diamond Series Flammable Storage Refrigerator 30 Cu. Ft. capacity One solid swing door, right hinged, not reversible Microprocessor temperature controller Adjustable operating temperature range: 1°C - 10°C Touch Screen Digital Temperature Display with user friendly interface Alarm Module with battery back-up to support temperature monitoring and alarms Password-protected control panel Sample simulated digital temperature display; .1° Resolution, adjustable temperature display in Celsius or Fahrenheit Active temperature scale bar display Resettable 1-point min/max history Digital 24-hour temperature chart Temperature data logging USB port for data transfer and software updates Real-time operational display clock 4-20mA output Electronic troubleshooting guide Electronic QR Code to access Owner's Manual & technical support contact information Adjustable alarm volume Audible and visual high/low temperature alarms Sensor error alarm Power failure alarm Door ajar alarm Low battery alarm Operation indicator Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back Remote alarm contacts Five adjustable shelves Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle Leveling legs One probe access port (3/8") White textured cabinet and door High density urethane foam cabinet and door insulation CFC-free refrigerant (R404a), foam insulation and packaging Three year parts and labor warranty Exterior dimensions: 35 ¾"W x 35"D x 78 ½"H Cycle defrost 115V, 60 Hz, 6 Amps, 1/3 HP UL/C-UL listed
i	Units meet NFPA guidelines 45 and 70
	Remote alarm contacts Five adjustable shelves Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle Leveling legs One probe access port (3/8") White textured cabinet and door High density urethane foam cabinet and door insulation CFC-free refrigerant (R404a), foam insulation and packaging Three year parts and labor warranty Exterior dimensions: 35 3/4"W x 35"D x 78 1/2"H Cycle defrost 115V, 60 Hz, 6 Amps, 1/3 HP