

Product Name:	PF021WWWLH/0A
Description:	<p>White Diamond Series Countertop Auto Defrost Freezer Freestanding-LEFT HINGED</p> <p>1.3 Cu. Ft. Capacity</p> <p>One solid swing door, left hinged</p> <p>Microprocessor temperature controller</p> <p>Digital temperature display</p> <p>Audible and visual high and low temperature alarms, with battery back up</p> <p>2 probes; 1 in air and 1 in sample bottle</p> <p>Remote alarm contacts</p> <p>Adjustable operating temperature range: -15°C – -25°C</p> <p>Auto defrost cycle every 6 hours, max air temp in empty freezer: +4.34°C; max air temp in loaded freezer: -2.89°C. Max sample temp in empty freezer: -4.76°C; max sample temp in loaded freezer: -9.58°C.</p> <p>2 adjustable shelves with guard rail to prevent product from being pushed against back wall</p> <p>Bottom footed shelf to allow air circulation</p> <p>Keyed door lock</p> <p>Magnetic door gasket for positive seal</p> <p>Leveling legs</p> <p>Probe access port (3/8")</p> <p>Powder coat exterior</p> <p>High density urethane foam cabinet and door insulation</p> <p>HFC-free refrigerant (R600a), foam insulation and packaging</p> <p>Three year parts and labor warranty, plus an additional two year compressor parts only warranty</p> <p>Pyxis[®], Omnicell[®] and AcuDose RX[®] compatible</p> <p>Exterior dimensions: 23 3/4"W x 24"D x 20 3/8"H</p> <p><i>Note: This unit must have 4" clearance on sides and back for adequate ventilation</i></p> <p>Auto defrost</p> <p>115V, 60 Hz, 1 Amp, 1/8 HP</p> <p>ENERGY STAR CERTIFIED</p> <p>ADA compliant</p> <p>UL/C-UL listed</p> <p>Shipping weight: 106 lbs.</p> <p>DISCLAIMER: Auto defrost freezers incorporate an electric heater installed on the evaporator that assist in the removal of the frost and ice. Although the heater helps speed up the frost and ice removal, it can raise the temperatures within the freezer.</p>