Description: Corepoint Scientific™ White Diamond Series Undercounter Auto Defrost Freezer Built-In 4.2 Cu. Ft. Capacity One solid swing door, right hinged* Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms 2 probes; 1 in air and 1 in glycol bottle Adjustable operating temperature range: -15°C – -25°C Auto defrost cycle every 6 hours, max air temp in empty freezer: +4.34°C; max air temp in loaded freezer: -9.58°C. Three adjustable shelves with guard rail on back to prevent product from being pushed against the back wall Back wall evaporator cover Keyed door lock Heavy duty door handle Magnetic door gasket for positive seal Leveling legs Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R290), foam insulation and packaging Three year parts and labor warranty, plus an additional two year compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 23 3/4" W x 24 ½" D x 33 1/8"H Auto defrost 115V, 60 Hz, 1.8 Amps 1/8 HP UL/C-UL listed Shipping weight: 143 lbs. *This product is available left hinged, product number PF051WWWLH/0A DISCI 4MBEP: Auto defrost freezers incorporate an electric beater	Product Name:	PF051WWW/0A
Freezer Built-In 4.2 Cu. Ft. Capacity One solid swing door, right hinged* Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms 2 probes; 1 in air and 1 in glycol bottle Adjustable operating temperature range: -15°C – -25°C Auto defrost cycle every 6 hours, max air temp in empty freezer: +4.34°C; max air temp in loaded freezer: -2.89°C. Max sample temp in empty freezer: -4.76°C; max sample temp in loaded freezer: -9.58°C. Three adjustable shelves with guard rail on back to prevent product from being pushed against the back wall Back wall evaporator cover Keyed door lock Heavy duty door handle Magnetic door gasket for positive seal Leveling legs Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R290), foam insulation and packaging Three year parts and labor warranty, plus an additional two year compressor parts only warrantyPyxis [®] , Omnicell [®] and AcuDose RX [®] compatible Exterior dimensions: 23 3/4" W x 24 ½" D x 33 1/8"H Auto defrost 115V, 60 Hz, 1.8 Amps 1/8 HP UL/C-UL listed Shipping weight: 143 lbs. *This product is available left hinged, product number PF051WWWLH/0A		
installed on the evaporator that assist in the removal of the frost and ice. Although the heater helps speed up the frost and ice removal, it can raise the temperatures within the freezer.		Corepoint Scientific [™] White Diamond Series Undercounter Auto Defrost Freezer Built-In 4.2 Cu. Ft. Capacity One solid swing door, right hinged* Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms 2 probes; 1 in air and 1 in glycol bottle Adjustable operating temperature range: -15°C – -25°C Auto defrost cycle every 6 hours, max air temp in empty freezer: +4.34°C; max air temp in loaded freezer: -2.80°C. Max sample temp in empty freezer: -4.76°C; max sample temp in loaded freezer: -9.58°C. Three adjustable shelves with guard rail on back to prevent product from being pushed against the back wall Back wall evaporator cover Keyed door lock Heavy duty door handle Magnetic door gasket for positive seal Leveling legs Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R290), foam insulation and packaging Three year parts and labor warranty, plus an additional two year compressor parts only warranty Pyxis [®] , Omnicell [®] and AcuDose RX [®] compatible Exterior dimensions: 23 3/4" W x 24 ½" D x 33 1/8"H Auto defrost 115V, 60 Hz, 1.8 Amps 1/8 HP UL/C-UL listed Shipping weight: 143 lbs. *This product is available left hinged, product number PF051WWWLH/0A DISCLAIMER: Auto defrost freezers incorporate an electric heater installed on the evaporator that assist in the removal of the frost and ice. Although the heater helps speed up the frost and ice removal, it can raise