D 1 (M	DDE400AUAYO/00AD
Product Name:	PRF122WWG/0CAD
Description:	Corepoint Scientific™ White Diamond Series Refrigerator & Freezer Combination with Controlled Auto Defrost Freezer
	12 Cu. Ft. capacity (10.5 Ref./1.0 Freezer)
	Two exterior swing doors (glass door refrigerator/solid door freezer),
	right hinged, not reversible
	Microprocessor temperature controller, refrigerator and freezer Digital temperature display with sample simulated probe, refrigerator and
	freezer
	Adjustable operating temperature range:
	Refrigerator: 36°F - 46°F (2°C - 8°C)
	Freezer: 5°F – -13°F (-15°C – -25°C) Defrost:
	Auto defrost cycle every 6 hours: (at Set Point -11°F /-24°C)
	Max air temp in empty freezer: 5°F (-15°C)
	Max air temp in loaded freezer: 3°F (-16°C)
	Max sample temp in empty freezer: 0°F (-18°C)
	Max sample temp in loaded freezer: -4°F (-20°C)
	Refrigerator/Freezer freestanding thermometer with 3 year certificate
	of calibration, with min/max memory, °F/°C switchable Audible and
	visual high and low temperature alarms, refrigerator and freezer
	Remote alarm contacts, refrigerator and freezer
	Six adjustable shelves with guard rail on back to prevent product from
	being pushed against back wall, Refrigerator
	Two adjustable shelves with guard rail on back to prevent product from
	being pushed against back wall, Freezer
	Bottom footed shelf to allow air circulation, Refrigerator and Freezer
	Vaccine storage power cord warning label
	Forced draft circulation Refrigerator
	Keyed door locks
	Magnetic door gasket for positive seal
	Integrated door handles
	Leveling legs
	Stacking kit
	LED interior light (Refrigerator)
	Two probe access ports (3/8"); one, refrigerator/one, freezer
	White powder coated exterior
	HFC-free refrigerant (R600a), foam insulation and packaging
	Pharmacy refrigerator/freezer toolkit and temperature logs
	Three year parts and labor warranty, plus an additional two year
	compressor parts warranty
1	Pyxis <sup>®</sup> , Omnicell <sup>®</sup> and AcuDose RX <sup>®</sup> compatible Exterior dimensions: 23 ¾"W x 26 ½" D x 80 ¼"H
	Controlled Auto Defrost freezer, Patented Technology
	Cycle defrost refrigerator
	115V, 60 Hz, 2.3 Amps refrigerator, 1 Amp freezer, 1/3 HP refrigerator,
	1/8 HP freezer

UL/C-UL listed Shipping weight: 289 lbs. In stock, with next day shipping *Please note this unit requires 2 outlets.